




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6 : H04M 19/00	A1	(11) International Publication Number: WO 95/08239 (43) International Publication Date: 23 March 1995 (23.03.95)
<p>(21) International Application Number: PCT/GB94/01896</p> <p>(22) International Filing Date: 1 September 1994 (01.09.94)</p> <p>(30) Priority Data: 93307255.5 15 September 1993 (15.09.93) EP (34) Countries for which the regional or international application was filed: GB et al.</p> <p>(71) Applicant: BRITISH TELECOMMUNICATIONS PUBLIC LIMITED COMPANY [GB/GB]; 81 Newgate Street, London EC1A 7AJ (GB).</p> <p>(72) Inventors: BUTLER, David; 9 Meadow Close, Trimley St Martin, Ipswich, Suffolk IP10 0UL (GB). FROST, Peter, Lewis, John; 14 Copswood Close, Kesgrave, Ipswich, Suffolk IP5 7QF (GB).</p> <p>(74) Agent: PRATT, David, Martin; BT Group Legal Services, Intellectual Property Department, 13th floor, 151 Gower Street, London WC1E 6BA (GB).</p>		<p>(81) Designated States: AU, CA, CN, JP, KR, NZ, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).</p> <p>Published With international search report.</p>

(54) Title: POWER SUPPLY CONTROLLER FOR AN OPTICAL FIBRE TELECOMMUNICATIONS SYSTEM



(57) Abstract

The power supply unit (1) of an optical fibre telecommunications network distribution point is provided with a power supply controller comprising a switch (2), a plurality of power supply lines (4) interconnecting the switch and power supply units in the premises of a plurality of customers, and control means (6) for controlling the supply of power from the power supply lines to the power supply unit of the distribution point.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

- 1 -

power supply controller for an optical fibre telecommunications system

This invention relates to a power supply controller for use in an optical fibre telecommunications network.

5 Throughout this specification, the term "optical" is intended to refer to that part of the electromagnetic spectrum which is generally known as the visible region, together with those parts of the infra red and ultra violet regions which are capable of being transmitted by dielectric
10 waveguides such as optical fibres.

An optical fibre telecommunications network is used to distribute information (optical signals) from one or more transmitting stations to one or more receiving stations. For telecommunications purposes, a passive optical network (PON),
15 such as TPON (telecommunications over a passive optical network), is advantageous in that it permits telecommunications over a network using a single transmitter (a laser located at exchange connected to the network). The main advantage of TPON is that it enables the sharing of
20 optical network fibres, and the opto-electronic equipment that serves them. TPON involves the use of optical splitter to pass optical signals from the exchange laser to receivers (typically telephones) at the customers' premises. A preferred split level is a 32-way split, accomplished by a
25 four-way split at the cabinet level, and by eight-way splits at the four distribution points (DPs) fed by the cabinet.

In a preferred form of TPON, known as street TPON, the final drop to the customers is by copper pairs, and the fibre terminates at the DPs. In this case, each DP is provided
30 with opto-electronic conversion/switching equipment, and this equipment needs to be powered electrically.

One way of powering such equipment would be to provide a mains electricity feed. The disadvantage of this is the expense involved in providing the transformer and control
35 equipment necessary to power the opto-electronic conversion/switching equipment. Moreover, as DPs are commonly sited at the tops of poles, this transformer and

- 2 -

control equipment would have to be sited in footway boxes, and this leads to high installation costs. Similarly, the provision of batteries to power the opto-electronic conversion/switching equipment would lead to high
5 installation costs, as these too would need to be sited in the ground.

The aim of the invention is to provide a way of powering this equipment.

The present invention provides a power supply
10 controller for the power supply unit of an optical fibre telecommunications network distribution point, the power supply controller comprising a switch, a plurality of power supply lines interconnecting the switch and power supply units in the premises of a plurality of customers, and
15 control means for controlling the supply of power from the power supply lines to the power supply unit of the distribution point.

The controller may further comprise line monitoring means for monitoring the voltage on each of the power supply
20 lines, the control means being such as to prevent power being supplied to the power supply unit of the distribution point from a given power supply line if the voltage on that supply line does not lie within a predetermined voltage range.

Advantageously, the control means controls the line
25 monitoring means so as to monitor the power supply lines cyclically in a predetermined order, and so that, for each monitoring cycle, the switch is controlled to switch power from those power supply lines whose voltage lies within said predetermined range to the power supply unit of the
30 distribution point one after another. Preferably a microprocessor constitutes the control means.

Conveniently, the line monitoring means is constituted by a respective line monitoring integrated circuit associated with each of the power supply lines.

35 The controller may further comprise interface means between the power supply lines and the switch, the interface means including a respective bridge rectifier associated with

- 3 -

each of the power supply lines. Preferably, the interface means also constitutes an interface between the power supply lines and the line monitoring means.

5 A power supply controller for controlling the power supply to the opto-electronic conversion/switching equipment within a street TPON DP, and constructed in accordance with the invention, will now be described, by way of example, with reference to the accompanying drawing, the single figure of which is a block circuit diagram of the controller.

10 Referring to the drawing, a power supply controller for a street TPON DP includes a power supply unit (PSU) 1 for powering the TPON multiplexer (not shown) of the DP. The PSU 1 is rated to output 24 volts dc. The DP PSU 1 is itself powered, via a switch 2 and a customer interface card 3, by
15 PSUs (not shown) in the eight customer premises associated with the DP. Each customer PSU is connected to the interface card 3 via a respective supply line 4, and the interface card has corresponding output lines 5 which lead to respective terminals 2a of the switch 2.

20 The customer PSUs are nominally rated at 50 volts, but the lengths of the lines 4 leading to the customer interface card 3 may reduce the voltages input to the DP PSU 1 to about 28 volts. Moreover, as the supply lines 4 are likely to be of different lengths, the voltages on the supply lines will
25 also tend to be different. The customer interface card 3 includes bridge rectifiers, one per supply line 4, to prevent one line feeding any of the other lines, and also to prevent a power failure on a given line affecting any of the other lines. The switch 2 also has a terminal 2b which is
30 connected to the DP PSU 1, and a contact 2c for connecting the terminal 2b optionally to any one of the terminals 2a. The switch 2 is controlled by a processor 6 and a voltage monitoring circuit 7. The processor 6 is a single chip microprocessor such as a 1468052E (an 8-bit CMOS
35 microprocessor containing a central processing unit, 112 bytes RAM, 16 input/output lines, an on-chip counter, and 8K of addressing space). The circuit 7 has a respective voltage

- 4 -

monitoring integrated circuit (not shown) connected to each of the output lines 5 via a respective line 8.

In use, the voltage monitoring circuit 7 checks the voltage on the supply lines 4 for suitability. A suitable voltage is one which is within predetermined voltage limits, and in particular does not fall below 27.5 volts. The processor 6 controls the switch 2 to select each suitable supply line 4 in turn, the check for suitability occurring just prior to the actual selection. If a given supply line 4 is suitable, it is used to power the DP PSU 1 by connecting the terminal 2b of the switch 2 to the appropriate customer terminal 2a using the contact 2c. If a given supply line 4 is unsuitable, the processor 6 reconfigures the switch 2 to avoid that supply line. Each supply line 4 is, however, checked in turn, so that, as soon as a previously-unsuitable supply line is again suitable, it will be selected next time it is checked. If the arrangement is such that each supply line 4 is selected for a period of one second each time its voltage is suitable, the DP PSU 1 has a 24 volt dc stable output, for all combinations of customer supply line circumstances, even when only one customer supply is suitable.

An important feature of the power supply controller described above is that the voltage checks and switch reconfigurations are carried out in real time. In this way, power can always be guaranteed to the DP PSU 1, even when only a single customer's supply line 4 is suitable. Should all customer supply lines 4 be unsuitable, or fail due to a power cut, an alarm signal is generated at the instigation of the processor 6, and this could be used to switch in battery backup power supplies (not shown) for the customer PSUs.

The processor 6 also logs the duration of each time each supply line 4 is accessed. This information is downloaded to the exchange at regular intervals (say every night), and forms the basis of a rebate system for the customers. In this way, customers can be recompensed for actual electricity usage, rather than on the basis of a fixed

- 5 -

rate of anticipated use.

It will be apparent that the power supply controller described above could be modified. For example, the simple relay switches 2a, 2b, 2c could be replaced by semiconductor switches. Also, the processor 6 could be programmed to monitor each customer's supply line 4 in order for it to decide what switching sequence to implement. The processor 6 would then select a switching sequence that will sample valid lines and miss out the rest. The switching sequence is re-calculated upon every loop, so again real time operation results. Thus, there is no appreciable delay between the monitoring process and the switching sequence, as the controller dynamically tracks the status of each supply line 4.

15

CLAIMS

1. A power supply controller for the power supply unit of an optical fibre telecommunications network distribution point, the power supply controller comprising a switch, a plurality of power supply lines interconnecting the switch and power supply units in the premises of a plurality of customers, and control means for controlling the supply of power from the power supply lines to the power supply unit of the distribution point.

2. A controller as claimed in claim 1, further comprising line monitoring means for monitoring the voltage on each of the power supply lines, the control means being such as to prevent power being supplied to the power supply unit of the distribution point from a given power supply line if the voltage on that supply line does not lie within a predetermined voltage range.

3. A controller as claimed in claim 1 or claim 2, wherein the control means controls the line monitoring means so as to monitor the power supply lines cyclically in a predetermined order, and so that, for each monitoring cycle, the switch is controlled to switch power from those power supply lines whose voltage lies within said predetermined range to the power supply unit of the distribution point one after another.

4. A controller as claimed in any one of claims 1 to 3, wherein a microprocessor constitutes the control means.

5. A controller as claimed in any one of claims 1 to 4, wherein the line monitoring means is constituted by a respective line monitoring integrated circuit associated with each of the power supply lines.

6. A controller as claimed in any one of claims 1 to 5,


- 7 -

further comprising interface means between the power supply lines and the switch, the interface means including a respective bridge rectifier associated with each of the power supply lines.

5

7. A controller as claimed in claim 6 when appendant to any one of claims 2 to 5, wherein the interface means also constitutes an interface between the power supply lines and the line monitoring means.

10



INTERNATIONAL SEARCH REPORT

Intern. Application No

PCT/GB 94/01896

A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 H04M19/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 H04M H04Q H04L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	INTERNATIONAL CONFERENCE ON COMMUNICATIONS - CONFERENCE RECORD (CAT. NO.91CH2984-3), vol.2, 23 June 1991, DENVER, CO - USA pages 929 - 935 S. FISHER 'powering active nodes in active loops' see paragraph 4.4 ---	1-7
A	EP,A,0 468 631 (GPT LIMITED) 29 January 1992 see abstract; figure 1 ---	1-7
-/--		

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

Z document member of the same patent family

Date of the actual completion of the international search

11 November 1994

Date of mailing of the international search report

28.11.94

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+31-70) 340-3016

Authorized officer

Montalbano, F

INTERNATIONAL SEARCH REPORT

Intern. Application No

PCT/GB 94/01896

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	INTELEC 91- THIRTEENTH INTERNATIONAL TELECOMMUNICATIONS ENERGY CONFERENCE (91CH2970-2), 5 November 1991, KYOTO, JAPAN pages 314 - 321, XP314599 Y.KUWATA ET AL. 'power supplies for fiber optic subscriber systems' see figure 1 ---	1-7
A	INTELEC 91 - THIRTEENTH INTERNATIONAL TELECOMMUNICATIONS ENERGY CONFERENCE (91CH2970-2), 5 November 1991, KYOTO, JAPAN pages 65 - 69, XP314559 H.N. WEINTROB 'power applications for non-central office applications in the united states - a tutorial' see paragraph 6.3 -----	1-7

INTERNATIONAL SEARCH REPORT

information on patent family members

Inter. Appl. Application No

PCT/GB 94/01896

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP-A-0468631	29-01-92	AU-B- 642277	14-10-93
		AU-A- 8136591	30-01-92
		CN-A- 1058501	05-02-92
		GB-A, B 2249239	29-04-92

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record.**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.